

HD Mega DVR 2U

Make Video Recoding Easy and Simply Brilliant

he HD MegaDVR 2U, an all interface in one full HD Digital Video Recorder, is industry's most versatile high definition recorder solution. It combines superior image and video quality, all versatile inputs, extensive easy control, various removable storage medias and a rage of innovative features.

MegaDVR can record high-definition crisp1080p video from any video sources, analog to digital. Saves extremely clear still images and videos to an internal removable HDD, external USB HDD, USB Flash, SD Card or network. With HDD, it can record can record highest quality HD video up to two weeks. Three level record quality is available. On board gain adjustable omni-directional microphone, buzzer and full color LED feedback are also available.

Meanwhile, MegaDVR supports real time streaming by connecting to the Ethernet network. It enables the live video to remote side for training or monitoring purposes.

MegaDVR is small size, universal and easy operation, no special training is required. It is just plug and play. Besides the foot pedals, LANC remote control is also available, it can provide extension cable length and recording status feedback.

MegaDVR has universal video connectivity and compatibility, the multiple video input formats enable compatibility and integration with virtually all legacy and up to date video sources. It accepts a wide range of video interfaces and types: CVBS, YPbPr, DVI, VGA, S-Video, HD/3G SDI, HDMI an well as 1080i50/60 or 1080p50/60. It also has SDI loop output and local DVI preview output.

The MegaDVR can be used in almost unlimited number of situations, CCTV surveillance, industrial imaging, education, training, etc. The MegaDVR allows you to easily record digital video and images directly to a flash drive or hard drive. You can archive and share your recordings on a Ethernet networks, enhance them with third-party editing programs, etc.



Features:

- ♦ Easily record crisp 1080p video and images
- ♦ High quality HD video in H.264 or MPEG4 format
- ♦ Simple to use, no special training required
- $\diamond\,$ Universal interface, works with almost all video interfaces
- \diamond Universal storage, works with all major USB Flash Drive, SD Card, USB HDD and SATA HDD
- ♦ Support Full HD up to 1080p@60fps
- Video Bit Rate up to 12Mbps
- ♦ HD/3G SDI input supported
- ♦ DVI preview output and SDI loop output
- ♦ 3 level gain adjustable Omni-direction microphone
- ♦ Still Image Photo
- ♦ Unique LANC remote control interface
- ♦ Foot pedal supported
- ♦ Internal removable SATA HDD
- ♦ keyboard to input patient data
- ♦ Network supported for live video streaming
- $\diamond\,$ Real-time Clock, Time/date stamp and OSD
- $\diamond\,$ Small size and low cost
- o upgradeable firmware





HD Mega DVR

All Universal Interface in one DVR

Power :

Power Adapter

: AC 100-240V 1A 50/60Hz 3 prong AC Jack

Video and Photo :

Video Encoder	: H.264/HP, MPEG-4/SP
Resolution	: 1920x1080@25/30/50/60fps
	1280x720@50/60fps
	480i/576i, 1080i@50/60
	SMPTE 425M/295M/274M/296M
Bit Rate	: Max. 12Mbits/s, 3 level adj.
Frame Rate	: 24/25fps/30fps, 50/60fps
Codec	: H.264/MPEG4, .avi file format
Rate Control	: CBR/VBR
Photo	: Jpeg
Streaming	: RTSP, RTMP

Audio :

Sampling	: 16KHz, 16bits
Codec	: AAC Stereo
Channels	: 2, with Automatic Gain Control
MIC	: 2.2VDC Bias, 2.2Kohm, <0.7VRмs
	-36dB. MIC gain adj.

Interface :

HD/3G SDI Input	: 1x BNC, 75ohm, 800mVpp
Component Input	: 3x BNC, YPbPr,75ohm
VGA Input	: 1 x 15 DE via DVI/VGA Adapter
DVI Input	: 1 x DVI-D
CVB Input	: 1 x BNC, 75ohm, 1Vpp
S-Video Input	: 1 x 4pin Mini-DIN
HDMI Input	: 1 x TYPE A, Receptacle
Preview Output	: 1 x DVI-D, Receptacle
SDI Loop Output	: Loop out HD/3G SDI, 75ohm, 800mVpp
Front MIC In	: Mono, Omni-directional
Back MIC In	: 2CH, 2 x 3.5mm Jack, External
Audio In	: 2CH, 2 x 3.5mm Jack, 20Kohm higher
Audio Out	: 2CH, 2 x 3.5mm Jack, 16ohm
Network	: RJ45, 10/100 Ethernet
Network Stack	: RTSP, HTTP
USB	: 3 x USB 2.0, 1 x front, 2 x rear
LANC Control	: 2.5mm LANC Jack
Foot Pedal	: 2 x 3.5mm Jack, 1x Photo, 1 x Video
Visible	: Full-color LED
Alert	: Buzz
LCD	: 2.4" TFT for video preview
Button	: Sealed Membrane

Software :

Firmware :

: Upgradeable, Linux OS.

Storage :

Internal	: 2.5" SATA HDD Removable
External	: USB Flash Drive, USB HDD, SD
Disk Format	: FAT32

Configuration :

Setting	: LCD or Network
Keyboard	: External

System requirements (Playback):

- USB 2.0/3.0 Interface
- USB 2.0/3.0 SDHC Card Reader
- USB 2.0/3.0 SATA Reader
- SDHC card interface
- Monitor resolution: 1920x1080

Physical and Environment

Size : Standard 2U, depth 17.5cm(6.9") Aluminum case

Weight : 2.9kg (6lb 4.7oz) (No HDD) Operating: 0°C to 45°C(32°F to 113°F) Storage : -20°C to 60°C(-4°F to 140°F)

Accessories

DVI Video Cable Power Cord DVI to VGA Adapter SDI Loop Out Terminator Plug MegaDVR User Guide *Foot Pedal *LANC Remote Control *HD/3G Bullet Camera *Accessories is optional and sold separately.



* All specifications are preliminary, subject to change without notice. * Accessory supply may be different for different product options.

* Actual object may differ from what you see from the catalog.