

Bullet 1080p HD SDI Camera with CS Mount

World's smallest HD SDI Bullet Camera witch CS Mount

he full HD 1080p SDI Bullet camera with CS Mount, the world's smallest, lightest SDI Bullet Camera, is one universal HD camera designed for surveillance, industrial, sports or any mobile applications. It is small size, light weight, universal CS lens, high sensitivity and low power consumption. It can capture beautiful, crisp 1080p video into SDI signal. With CS Mount, any industrial standard CS mount lens from fix to zoom can be installed for critical or creative applications.

The greatest advantage of SDI camera is fully digital, high quality, low latency, robust video over long distance coaxial cable. It is a best solution for a broad range of business and industrial video applications where long distance, high definition video transmission is required, such as machine vision, video con-

Features:

- ♦ 2 Megapixel full HD 1080p Bullet Camera
- ♦ Universal C/CS Mount
- ♦ HD SDI output up to 100 meters
- ♦ Low light 1/3" high sensitive sensor
- ♦ High Quality ISP with OSD menu options
- No video distortion and latency
- ◇ Rugged Aluminum case
- ◇ Broad range of CS lens are available

Power:

Consumption Voltage	: 180mA at 12VDC : 12VDC +/-10%
Video : Output	: HD-SDI, 1.485Gb/s 1080p 25/30fps
Interface :	
Video	: SDI, BNC 75ohm, 800mVpp Optional Lock connector
Power	: 5.5mm Jack x 2. 0mm I.D
	Optional Power over coaxial
OSD	: Built in
Button	: 5 direction key, optional
Remote	: UART/RS485 for module

Physical and Environment

Body Size	: 70x28mm(2.75" x Ф1.1")
	Sand blast black aluminum
Weight	: 68g(2.4oz)
Temp.	: 0°C to 45°C in flow air



Camera:

Junioran		
Sensor	: CMOS, 12bit image	
Size	: 1/3"	
Active Pixels	: 1920x1080, 2.2um pixel size	
Scanning System	: Progressive Scan	
Lens*	: Broad range of lens available	
Lens Mount	: C/CS Mount	
Sensitivity	: 3300 mv/lux-sec	
Dynamic Range	: 69db	
Shutter	: Rolling shutter	
Exposure Control	: AE/MANUAL, AWB/MANUAL	
BLC/HSBLC	: Yes	
AGC	: High/Medium/Low	
Day&Night	: Yes	
Adjust	: Brightness/Sharpness	
2D/3D NR	: Yes	
WDR/D-WDR	: Yes	
Defog	: Yes	
Privacy Masking	: Yes	
Digital zoom	: Yes	
Multi-Language	: Yes	
OSD	: Yes	
*Camera with menu setting is not weatherproof		

Accessories

Power Adapter Bike Mount *Accessories is optional and sold separately.

